



**QUOTATION NOTICE**

Sealed quotations are invited for the supply of following items with the under mentioned specifications in the Kudumbashree, Head office.

Sl No	Product Description	Qty
1	<p><b>BOX</b> 12" 1300W Powered Speaker, 1300W System Power, Dynamic bass response Technology lows, Built-in 2-channel wide-z mixer accepts mic, line and instrument Signals, Four application-specific speaker modes for instant system optimization heavy use, Stand, Cables, etc.</p> <p>Item Weight 16.1 Kg Product Dimensions 35.6 x 35.8 x 61.5 cm Colour Black Speaker Amplification Type active Audio Wattage 1300 Size 12inchA Voltage 100</p>	2
2	<p><b>Mixer</b> 12ch professional effects mixer</p> <p>Item Weight 4.1 Kg Product Dimensions 37 x 35.8 x 9.1 cm Body Material steel Colour Black Material Steel</p> <p>ReadyFX effects engine with 16 effects including reverbs, delays, and choruses, 7-band graphic EQ for tuning mains or monitors Aux output for monitor mixes, venue 70-volt systems, and more 3-band EQ and 100Hz low-cut filter on all channels</p>	1
3	<p><b>2-channel stereo power amplifier</b> 2500W 2-Channel Stereo Power Amplifier Stereo output: 1400W @ 2 ohms, 750W @ 4 ohms, 575W @ 8 ohms Mono output: 2500W @ 4 ohms, 1500W @ 8 ohms Professional stereo power amplifier with high-power / ultra low-noise design Fast Recovery circuitry reduces distortion at the edge of clipping and beyond Independent defeatable Limiter protection per channel Subsonic Filter for maximum amplifier efficiency, XLR and 1/4" input connections, Speakon and Binding Post output connections, Robust, impact-resistant, all-steel 2U rackmount chassis, 3-year full warranty</p>	1

4	<u>Wireless MicroPhone &amp; colar mic</u> Receiver : Dual Channel Non-Diversity Frequency response : 50Hz-16KHz Polar Pattern (Hand mic) : Cardioid Output : Individual Channel: XLR, Mix out: ¼" Jack Power Req. (Hand mic) : 2 x 1.5V AA Receiver : 240V AC 50Hz for AC Adaptor Supplied with the set	3
5	<u>Microphone</u> Transducer Type : Dynamic Frequency Response : 40Hz-16kHz Polar Pattern : Super Cardioid Sensitivity (at 1kHz) : -52dB ±3dB Nominal Impedance : 600 Ω Connector : 3-pin XLR male Accessories Included : 6.5M XLR-F to XLR-M Mic Cable, Mic Holder	2

The quotation addressed to the Executive Director, Kudumbashree Head office should reach this office on or before 26/10/2018 at 3.00 P.M. The quotation thus received at the stipulated time shall be opened by the undersigned or authorized persons 3.30 P.M. on the same day and orders will be issued in the name of lowest bidder. The lowest bidder should supply the item within 7 days from the receipt of supply order.

The undersigned reserves the right to accept or reject any quotation without assigning any specific reason there on.

Sd/-  
**Executive Director**  
**Kudumbashree**

Copy to: -

1. Notice Board
2. Nearby shops for wide publicity
3. Stock/Spare File

**Approved for Issue**



**Administrative Officer**